

TITAN CVTF FLEX

Premium Performance CVTF specially designed for use in many CVT-gearboxes using push-belts or transmission chains made of steel.

Description

TITAN CVTF FLEX is a high-performance CVT transmission oil formulated with selected base oils for use in many CVT transmissions with steel chains or push-belts. It offers excellent wear protection, optimized low-temperature properties and stable friction characteristics over the entire drain interval.

Application

TITAN CVTF FLEX is field proven and has been tested in many continuously variable automatic transmissions of different manufacturers. The service intervals of the manufacturer must be observed.

TITAN CVTF FLEX is miscible and compatible with conventional branded CVTFs. However, intermixtures with other transmission oils should be avoided in order to fully utilize the product's benefits. Respectively a complete oil change is recommended when converting to TITAN CVTF FLEX. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

Advantages/Benefits

- universally applicable for many CVT transmissions of various manufacturers.
- offers excellent wear protection
- optimized low temperature properties
- very stable friction characteristics over the entire drain interval
- Specially developed additive components for good ageing and oxidation stability, as well as outstanding protection against foaming

Specifications

- -

Approvals

- -

FUCHS Recommendations

- BMW 83 22 0 136 376
- BMW 83 22 0 429 154
- CHRYSLER CVTF+4
- DAIHATSU AMMIX CVTF-DC/-DFE
- DODGE/JEEP NS-2/CVTF+4
- FORD WSS-M2C933-A/MERCON C
- GM 19260800
- GM DEX-CVT
- GM HP CVTF
- HONDA HCF-2
- HYUNDAI/KIA SP-CVT1
- MAZDA CVTF 3320
- MITSUBISHI CVTF-J1/J4
- NISSAN NS-1/NS-2/NS-3
- SUBARU Lineartronic CV-30/CVTF/CVTF II/E-CVT/iCVT
- SUZUKI TC/NS-2/CVT Green 1/CVT Green 2/CVTF 3320
- TOYOTA TC/CVT FE
- VW TL 521 80 (G 052 180)
- VW TL 525 16 (G 052 516)

PI60845e, PMA, 08.09.2021, Page 1

TYPICAL CHARACTERISTICS

Density at 15 °C	DIN 51757	0.850 g/ml
Kinematic Viscosity at 40°C	DIN 51562-1	35.0 mm ² /s
Kinematic Viscosity at 100°C	DIN 51562-1	7.3 mm ² /s
Viscosity-Index	DIN ISO 2909	170
Pourpoint	DIN ISO 3016	-48 °C
Product Dyeing	DIN 10964	none

PI60845e, PMA, 08.09.2021, Page 2

FUCHS LUBRICANTS (UK) PLC
New Century Street, Hanley
GB-Stoke-on-Trent, Staffordshire, ST1 5HU

Tel +44-1782 -20 37 00
Fax +44-1782 -20 20 73
contact-uk@fuchs-oil.com



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products