

TITAN SUPERSYN SAE 10W-60

Ultra High Performance, fuel-economy engine oil for passenger cars. Low oil consumption. Highly durable lubricating film and high oil pressure.

Description

TITAN SUPERSYN SAE 10W-60 is the high-viscosity engine oil of the TITAN SUPERSYN-range. It is based on innovative engine oil technology. The modern and reliable additive technology secures reliable performance at all operating conditions. This up to date Ultra High Performance Engine Oil can be used all over the year. The good cold flow properties of TITAN SUPERSYN SAE 10W-60 are providing fastest lubrication to all parts of the engine. Friction and wear will be effectively reduced due to a reliable oil film being generated. TITAN SUPERSYN SAE 10W-60 guarantees engine durability and improved oil pressure under city cycle mode as well as under top speed racing conditions.

Application

TITAN SUPERSYN SAE 10W-60 can be used for passenger cars and light duty vehicles with naturally aspirated or supercharged gasoline and diesel engines. Being an all season's motor oil, TITAN SUPERSYN SAE 10W-60 offers good cold start and fuel economy in the winter as well as high thermal stability in summer. TITAN SUPERSYN SAE 10W-60 is miscible and compatible with conventional branded engine oils. However, mixing with other engine oils should be avoided in order to fully utilize the product's benefits. A complete oil change is recommended when converting to TITAN SUPERSYN SAE 10W-60. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

Advantages/Benefits

- Multipurpose applicability in many vehicles
- Good cold start performance
- Very good engine cleanliness
- High thermal stability
- Low evaporation loss, low oil consumption
- Improved oil pressure even at high ambient temperatures
- Sustainable wear protection
- Thanks to its viscosity, it is also suitable for use in motorsport applications

Specifications

- -

Approvals

- -

FUCHS Recommendations

- ACEA A3/B3
- API SL/CF
- FIAT 9.55535-H3

PI60409e, PMA, 06.05.2022, Page 1

TYPICAL CHARACTERISTICS

Density at 15 °C	DIN 51757	0.865 g/ml
SAE grade	SAE J300	10W-60
Kinematic Viscosity at 40°C	DIN 51562-1	173 mm ² /s
Kinematic Viscosity at 100°C	DIN 51562-1	23.5 mm ² /s
Viscosity index	DIN ISO 2909	174
HTHS	CEC L-036-90	≥ 3.5 mPa*s
Sulphated ash	ASTM D874	≥ 0.9 and ≤ 1.5 % m/m
Product dyeing	DIN 10964	none

PI60409e, PMA, 06.05.2022, Page 2