

TITAN SUPERSYN F Eco-FE SAE 0W-30

Ultra High Performance, extreme fuel-economy engine oil especially developed for modern Ford Diesel engines. Excellent cold starting and lower oil consumption.

Description

TITAN SUPERSYN F Eco-FE SAE 0W-30 is an extreme energy conserving multigrade passenger car engine oil suitable for modern Ford diesel engines. The result of the high quality base oils in combination with our most up to date additive technology is this ultra-high performance engine oil. The special composition of TITAN SUPERSYN F Eco-FE SAE 0W-30 ensures excellent aging stability, optimum wear protection and outstanding cold-start properties over the entire oil change interval and due to the optimized high-temperature viscosity, TITAN SUPERSYN F Eco-FE SAE 0W-30 offers further potential for fuel savings and thus reduced CO₂ emissions.

Application

TITAN SUPERSYN F Eco-FE SAE 0W-30 has been developed for use in modern Ford diesel engines from model year 2014, which requires an oil according to the FORD WSS-M2C950-A specification. **TITAN SUPERSYN F Eco-FE SAE 0W-30 is not backward compatible with older Ford specifications!**

TITAN SUPERSYN F Eco-FE SAE 0W-30 is miscible and compatible with conventional branded engine oils. However, intermixtures with other engine oils should be avoided in order to fully utilize the product's benefits. Respectively a complete oil change is recommended when converting to TITAN SUPERSYN F Eco-FE SAE 0W-30. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

Advantages/Benefits

- Especially developed for modern Ford Diesel engines
- Outstanding cold-start properties
- Potential for fuel savings and thus reduced CO₂ emissions
- Suitable for extended oil change intervals
- Optimum wear protection

Specifications

- ACEA C2
- FORD WSS-M2C950-A

Approvals

- JAGUAR LAND ROVER STJLR.03.5007

FUCHS Recommendations

- -

TYPICAL CHARACTERISTICS

Density at 15 °C	DIN 51757	0.843 g/ml
SAE grade	SAE J300	0W-30
Kinematic Viscosity at 40°C	DIN 51562-1	45.8 mm ² /s
Kinematic Viscosity at 100°C	DIN 51562-1	9.6 mm ² /s
Viscosity Index	DIN ISO 2909	201
HTHS	CEC L-036-90	≥ 2.9 mPa*s
Pour Point	DIN ISO 3016	-45 °C
Sulphated ash	ASTM D874	≤ 0.8 % m/m
Product dyeing	DIN 10964	none

PI60710e, PMA, 28.06.2021, Page 2

FUCHS LUBRICANTS (UK) PLC
New Century Street, Hanley
GB-Stoke-on-Trent, Staffordshire, ST1 5HU

Tel +44-1782 -20 37 00
Fax +44-1782 -20 20 73
contact-uk@fuchs-oil.com



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products